

[First Hit](#) [Previous Doc](#) [Next Doc](#) [Go to Doc#](#)☐ [Generate Collection](#) [Print](#)

L4: Entry 36 of 101

File: JPAB

May 14, 1980

PUB-NO: JP355063997A
DOCUMENT-IDENTIFIER: JP 55063997 A
TITLE: AUTOMATIC NAVIGATION EQUIPMENT

PUBN-DATE: May 14, 1980

INVENTOR-INFORMATION:

NAME

COUNTRY

MIYABE, TOSHIHIDE

KAKIZAKI, YASUO

ASSIGNEE-INFORMATION:

NAME

COUNTRY

YOKOGAWA HOKUSHIN ELECTRIC CORP

APPL-NO: JP53137182

APPL-DATE: November 6, 1978

US-CL-CURRENT: 114/144RE

INT-CL (IPC): B63H 25/04

ABSTRACT:

PURPOSE: To make navigation automatically controllable by generating steering signals in such a way that self-bearing and position are measured, settled course to return to the predefined route, and the deviation between the settled course and the measured bearing.

CONSTITUTION: Self-bearing is measured by a bearing measurement instrument 12 to measure self-bearing, such as gyrocompass. And self-position is measured by a navigation satellite receiver 11, the settled course is calculated for returning to the predefined route. Then, the deviation $\Delta\theta$ is calculated between the settled course and the self-bearing measured by the bearing measurement instrument 12, this deviated signal is supplied as steering signal to an automatic steering arrangement 14. This steering signal controls opening and closing of electromagnetic valve of a steering gear 15 to make movements so that the deviation signal may be zero.

COPYRIGHT: (C) 1980, JPO&Japio

[Previous Doc](#) [Next Doc](#) [Go to Doc#](#)